



The City of Seattle

Pioneer Square Preservation Board

Mailing Address: PO Box 94649, Seattle WA 98124-4649

Street Address: 600 4th Avenue, 4th Floor

PSB 253/23

Staff REPORT

for Board meeting October 4, 2023

Board Members Please Note: The citations from the District Ordinance, Rules for the Pioneer Square Preservation District, and Secretary of the Interior's Standards listed below are for your consideration in addition to any other citations you find relevant in considering each application.

100423.41 **Triangle Building**
553 1st Ave S

Proposed rehabilitation of the building

Staff report: This is the first briefing for this project.

Code Citations:

Seattle Municipal Code

23.66.030 Certificates of Approval required

- A. Certificate of approval required. No person shall alter, demolish, construct, reconstruct, restore, remodel, make any visible change to the exterior appearance of any structure, or to the public rights-of-way or other public spaces in a special review district, and no one shall remove or substantially alter any existing sign or erect or place any new sign or change the principal use of any building, or any portion of a building, structure or lot in a special review district, and no permit for such activity shall be issued unless a certificate of approval has been issued by the Department of Neighborhoods Director.

23.66.140 Height

C. Rooftop features and additions to structures

1. The height limits established for the rooftop features described in this Section 23.66.140 may be increased by the average height of the existing street parapet or a historically substantiated reconstructed parapet on the building on which the rooftop feature is proposed.

3. The setbacks required for rooftop features may be modified by the Department of Neighborhoods Director, after a sight line review by the Preservation Board to

Administered by The Historic Preservation Program
The Seattle Department of Neighborhoods

"Printed on Recycled Paper"

ensure that the features are minimally visible from public streets and parks within 300 feet of the structure.

4. Height limits for rooftop features

b. For existing structures, open railings, planters, clerestories, skylights, play equipment, parapets, and firewalls may extend up to 4 feet above the roof of the structure or the maximum height limit, whichever is less. For new structures, such features may extend up to 4 feet above the maximum height limit. No rooftop coverage limits apply to such features regardless of whether the structure is existing or new.

c. Solar collectors, excluding greenhouses, may extend up to 7 feet above the roof of the structure or the maximum height limit, whichever is less, with unlimited rooftop coverage, provided they are a minimum of 10 feet from all lot lines. For new structures, solar collectors may extend up to 7 feet above the maximum height limit, except as provided in subsection 23.66.140.C.4.j.1, and provided that they are a minimum of 10 feet from all lot lines.

- d. The following rooftop features may extend up to 8 feet above the roof or maximum height limit, whichever is less, if they are set back a minimum of 15 feet from the street and 3 feet from an alley. They may extend up to 15 feet above the roof if set back a minimum of 30 feet from the street. A setback may not be required at common wall lines subject to review by the Preservation Board and approval by the Department of Neighborhoods Director. The combined coverage of the following listed rooftop features shall not exceed 25 percent of the roof area:
- 1) Solar collectors, excluding greenhouses;
 - 2) Stair and elevator penthouses;
 - 3) Mechanical equipment;

RULES FOR THE PIONEER SQUARE PRESERVATION DISTRICT

III. GENERAL GUIDELINES FOR REHABILITATION AND NEW CONSTRUCTION

In addition to the Pioneer Square Preservation District Ordinance and Rules, The Secretary of the Interior's Standards for Rehabilitation with Guidelines for Rehabilitating Historic Buildings, and the complete series of Historic Buildings Preservation Briefs developed by the National Park Service shall serve as guidelines for proposed exterior alterations and treatments, rehabilitation projects, and new construction. (7/99)

Rehabilitation is defined as the act or process of making possible a compatible use for a property through repair, alterations, and additions while preserving those portions or features which convey its historical, cultural, or architectural values. (7/99) In considering rehabilitation projects, what is critical is the stabilization of significant historical detailing, respect for the original architectural style, and compatibility of scale and materials.

The following architectural elements are typical throughout the District and will be used by the Board in the evaluation of requests for design approval:

- A. Site. The property line is the line of the building mass. Street facades are uniformly located at the front property lines, thus there is a strong street edge definition. Building cornices, bay windows and ornament project beyond the main wall surface of some facades.
- B. Design. Building design is generally typified by horizontal divisions which create distinctive base and cap levels. Facades may also be divided vertically by pilasters or wide piers which form repetitive window bays. Street facades are also distinguished by heavy terminal cornices and parapets, ornamental storefronts and entrance bays and repetitive window sizes and placement.
- C. Building materials. The most common facing materials are brick masonry and cut or rusticated sandstone, with limited use of terra cotta and tile. Wooden window sash, ornamental sheet metal, carved stone and wooden or cast iron storefronts are also typically used throughout the District. Synthetic stucco siding materials are generally not permitted. (7/99)
- D. Color. Building facades are primarily composed of varied tones of red brick masonry or gray sandstone. Unfinished brick, stone, or concrete masonry unit surfaces may not be painted. Painted color is typically applied to wooden window sash, sheet metal ornament and wooden or cast iron storefronts. Paint colors shall be appropriate to ensure compatibility within the District. (7/99)
- E. Building Base. Buildings are allowed a base of approximately 18-24 inches. Base materials should be concrete, sandstone, or granite, and may be poured, cut to fit or unit-paved. The color relationship between the sidewalk and building must be considered. Brick or tile materials should not be used except when existing walks are of the same material.
- F. Additions. Additional stories to existing buildings are discouraged unless they were original to the structure.

VIII. MECHANICAL SYSTEMS

The preferred location for mechanical systems is in the building interior. In cases where locating systems in the interior is not possible, exterior mechanical systems equipment, including but not limited to air conditioning units, compressors, boilers, generators, ductwork, louvers, wiring and pipes, shall be installed on non-primary building facades and/or roof tops. Mechanical equipment shall be installed in such a manner that character-defining features of the building are not radically changed, damaged, obscured, or destroyed. Screening and/or painting of equipment may be required to diminish negative visual impacts.

Secretary of Interior's Standards

1. A property will be used as it was historically or be given a new use that requires minimal change to its distinctive materials, features, spaces and spatial relationships.
2. The historic character of a property will be retained and preserved. The removal of distinctive materials or alteration of features, spaces and spatial relationships that characterize a property will be avoided.
3. Each property will be recognized as a physical record of its time, place and use. Changes that create a false sense of historical development, such as adding conjectural features or elements from other historic properties, will not be undertaken.
4. Changes to a property that have acquired historic significance in their own right will be retained and preserved.
5. Distinctive materials, features, finishes, and construction techniques or examples of craftsmanship that characterize a property will be preserved.
6. Deteriorated historic features will be repaired rather than replaced. Where the severity of deterioration requires replacement of a distinctive feature, the new feature will match the old in design, color, texture and, where possible, materials. Replacement of missing features will be substantiated by documentary and physical evidence.
7. Chemical or physical treatments, if appropriate, will be undertaken using the gentlest means possible. Treatments that cause damage to historic materials will not be used.
9. New additions, exterior alterations, or related new construction will not destroy historic materials, features, and spatial relationships that characterize the property. The new work will be differentiated from the old and will be compatible with the historic materials, features, size, scale and proportion, and massing to protect the integrity of the property and its environment.
10. New additions and adjacent or related new construction will be undertaken in such a manner that, if removed in the future, the essential form and integrity of the historic property and its environment would be unimpaired.

Issued: September 22, 2023

Genna Nashem

Pioneer Square Preservation Board Coordinator